



**5 Year Duration**

**List of Acceptable Plastics for  
Optical Lenses and Reflex Reflectors  
Used on Motor Vehicles**

March 6, 2026



TM

**AMECA**

**5 Year Duration**

**List of Acceptable Plastics for  
Optical Lenses and Reflex Reflectors  
Used on Motor Vehicles**

---

**March 6, 2026 Edition**

**Automotive Manufacturers Equipment Compliance Agency, Inc.  
1025 Connecticut Avenue, NW Suite #1000  
Washington DC 20036**

**[www.ameca.org](http://www.ameca.org)**

## 1. STATUS

The following materials have been accepted by the Automotive Manufacturers Equipment Compliance Agency as meeting the 5-year version of the weathering test of FMVSS 108 for plastics used in optical lenses and reflectors used on motor vehicles. No evaluation has been made as to the suitability of individual materials for particular automotive uses, or to the manufacturing methods.

***You must contact the resin or coating manufacturer to determine the best material for your application.***

***Every plastics resin manufacturer has specialized products for different applications, processing conditions, manufacturing equipment, light sources and final use.***

***Please contact the manufacturer directly for more information.***

The device manufacturers must ensure that the lenses molded from acceptable materials meet the color and plastic stability test requirements for each individual device.

## 2. LISTING

The material is listed by the manufacturer's name, trade name and flow formulation, type of resin, color number and color.

## 3. MATERIAL COATINGS and HAZE

When these materials are used for state/provincial regulated lighting device lenses, the applicable state/provincial regulations shall be met.

The Code "&" denotes material which must be coated to pass the 5 year weathering.

## 4. DISTRIBUTION

This list is updated and distributed free on a weekly basis. Any revised or pre-release editions may be obtained by contacting AMECA.

## 5. DEFINITIONS

Coating -- Material applied to surface of the lens to improve some aspect of performance.

Coated materials-- a material which has a coating applied to the surface of the finished sample to impart some protective properties. Coating identification means a mark of the manufacturer's name, formulation designation number, and recommendations for application.

Color bleeding -- the migration of color out of a plastic part onto the surrounding surface.

Cracking -- a separation of adjacent sections of a plastic material with penetration into the specimen.

Crazing -- a network of apparent fine cracks on or beneath the surface of materials.

Delamination -- a separation of the layers of a material including coatings.

Hard Coat -- 1) Coating which is cured by UV radiation.

2) Coating which provides additional resistance to abrasion or scratching which may be cured by thermally or by UV radiation. May contribute to long term durability of material.

**Note:** Both definitions are being used--please verify the intended performance when discussing hard coats.

Haze -- the cloudy or turbid appearance of an otherwise transparent specimen caused by light scattered from within the specimen or from its surface.

UV-protective Coat -- Coating designed to provide additional protection from the sun's electromagnetic radiation, particularly those wavelengths in the UV bandwidth. Often used on polycarbonate substrates to improve weathering performance. Polycarbonates must be coated for use in or in front of reflex reflectors.

Reflex reflectors-- devices used on vehicles to give an indication to approaching drivers using reflected light from the lamps of the approaching vehicle.

Substrate -- Base material to which all other performance enhancing materials are added.

UV radiation -- Short wavelength, high energy radiation emitted by the sun or other object (HID lamp). Wave lengths between 10 and 380 nm.

HID Lamp -- High Intensity Discharge Lamp. Lamps produce light by the use of a stabilized arc. Lamps can produce significant UV radiation which may require special materials. See SAE J1647

## 6. NOTE ON COLOR

The colors listed have been determined to be in compliance with SAE J-578 using the ASTM E 308-66 method required by FMVSS 108 or in thicknesses specified by the resin manufacturer

**NOT EVERY COLOR LISTED WILL MEET SAE J-578 COORDINATES  
FOR YOUR INTENDED THICKNESS**

**NOT EVERY MATERIAL IN EVERY COLOR WILL MEET J578 WITH  
LED OR ILLUMINANT C LIGHTSOURCES**

**CHECK WITH THE RESIN MANUFACTURER'S COLOR SPECIALIST**

The ASTM E 308-66 method uses an illuminant A light source energized to 2856k. *If you use anything other than an incandescent light source at 2856k you MUST verify that the resulting color meets the specifications of SAE J-578 for your intended thickness.* Halogen light sources at 3200k, illuminant C (strobe) and LED light sources can dramatically alter the color output. In addition, some light sources do not emit color or luminous flux uniformly. Measurements should be made to verify that the emitted light using your intended lightsource meets the specifications of J-578 throughout its photometric range.

## 7. NOTE ON INNER LENS COLOR

***Combinations of inner and outer lenses with various colors may not perform predictably. Output can change with different light sources. Check with the resin manufacturer's color specialist when making selections.***

## 8. NOTE ON "EQUIVALENT" FORMULATIONS.

Many companies have distributed manufacturing facilities, cooperative agreements or joint ventures. In order to list a facility or another company the company which has done the FIVE year weathering testing must send documentation stating that the materials, processes and end products are equivalent between itself and the new applicant. Due to industry complaints, the List of Acceptable Plastics has revised the listing to more accurately reflect the test data from various parent companies. ***In addition, if the joint venture is terminated or the manufacturing facility is sold, the subsidiary or joint company must be able to provide weathering test data on its own. A company can no longer rely on the parent company data and processes if they have no relationship to the parent company who conducted the original testing.***

## 9. NOTE ON SUBMITTING FOR ADDITIONAL COLORS

If you plan to add an additional color number to your listing, please list the existing colors which have undergone the FIVE year weathering that are a greater and lesser concentration. The colors listed MUST be in the same color space. FMVSS 108 S14.4.2.2.2

## 10. Note on Inner Lens Testing

Only inner and outer lens materials, tested together, may be registered for an inner lens system. Not every manufacturer's materials will qualify for the outer lens. Other manufacturers lens material may NOT be used as an outer lens even if those materials have successfully been used as an outer lens for a different material. The inner lens/coating and outer lens/coating must be tested together as a system.

Currently the DOT has issued no guidelines for inner lenses. If and when they do, they will be the requirements that everyone must follow. In the meantime, we would recommend for following guidelines for inner lens test setup.

- 1) You must bracket test every color combination (light/dark) you want to use—red, blue, amber, etc. The light/dark colors must be in the same color space.
- 2) You must bracket test molecular weight (heavy/light) for both outer lens and inner lens.
- 3) The test setup—airspace, ventilation, should duplicate as close as possible the conditions in an inner automotive lens including factors such as ventilation, spacing between inner and outer lens and coatings.
- 4) For more information, please see SAE Paper: <http://papers.sae.org/2004-01-0800>

Inner lens materials will be listed with their outer lens material jointly as a system. Both the inner lens and outer lens material/color will be listed with both materials specified. If you only test a limited range of lens colors, thicknesses or materials that is how they will be listed.

## 11. Special Note on the definition of "Protected Inner Lens" and/or "Protected Applications"

**Protected Inner Lenses or Protected Applications for polycarbonate lenses refers to an outer lens which has a UV absorbing capabilities. NOT physical protection but UV protection.**

## Frequently Asked Questions

Q1) If someone else has weathered a polycarbonate/PMMA material, do I have to weather my polycarbonate/PMMA material?

A) Yes, every company's material stands independently from what another company has done. Each coating, pigment and additive must be tested with each company's own material. Each separate material stands alone for weathering performance unless bracketed by materials of higher and lower concentrations or molecular weights.

Q2) If someone else has weathered a pigment with another plastic do I have to weather the pigment with my plastic?

A) Yes, every company's material stands independently from what another company has done. Each coating, pigment and additive must be tested with each company's own material. Each separate material stands alone for weathering performance unless bracketed by materials of higher and lower concentrations or molecular weights.

Q3) If someone else has weathered a coating do I have to weather my material with that coating?

A) Yes, every company's material stands independently from what another company has done. Each coating, pigment and additive must be tested with each company's own material. Each separate material stands alone for weathering performance unless bracketed by materials of higher and lower concentrations or molecular weights.

Q4) Testing laboratories typically use a 1-10 numbering scale according to ASTM D660 to indicate the degree of crazing, cracking or delamination associated with weathering. What numerical value from ASTM D660 is acceptable for listing?

A) FMVSS 108 does not refer to any numerical values from ASTM D660. The numerical values are done by the test laboratory for manufacture convenience. Sections from FMVSS 108 are below.

B)

S14.4.2.2.4.2 After completion of the outdoor exposure test materials used for headlamp lenses must show no deterioration.

S14.4.2.2.4.3 After completion of the outdoor exposure test all materials, when compared with the unexposed control samples, must not show physical changes affecting performance such as color bleeding, delamination, crazing, or cracking. **Additionally materials used for reflex reflectors and lenses used in front of reflex reflectors must not show surface deterioration or dimensional changes.**

Your tested samples must not show any changes affecting performance. The only value which shows no change is a numerical value of 10.

Q5) How many thicknesses to I have to test?

A) FMVSS 108: S14.4.2.1.3 Samples must be furnished in thicknesses of  $1.6 \pm 0.25$  mm,  $2.3 \pm 0.25$  mm,  $3.2 \pm 0.25$  mm, and  $6.4 \pm 0.25$  mm.

Q6) Even if it's for a coating?

A) Yes.

Q7) Do materials have to meet the color requirements before testing?

A) Yes: S14.4.2.1.4 All samples must conform to the applicable color test requirement of this standard prior to testing.

Q8) What about the plastics used in non-FMVSS applications such as emergency vehicle lighting which also require three year weathering?

A) Yes, those can be listed with non-standard colors as long as they are NOT used on FMVSS 108 lighting devices.

Testing outline. Note, we also recommend you send DOUBLE samples to prevent any errors.

► 4 Thicknesses

- For each colour
- For each coating
- For each molecular weight (MW)

► For example:

- 4 thickness samples of dark red, uncoated, Lowest MW
- 4 thickness samples of light red, uncoated, Lowest MW
- 4 thickness samples of dark red, uncoated, Highest MW
- 4 thickness samples of light red, uncoated, Highest MW
  
- 4 thickness samples of dark red, coating 1, Lowest MW
- 4 thickness samples of light red, coating 1, Lowest MW
- 4 thickness samples of dark red, coating 1, Highest MW
- 4 thickness samples of light red, coating 1, Highest MW
  
- Now repeat for clear, yellow, blue, coating 2 & coating 3

**AMECA 5 Year Duration**  
**List of Acceptable Plastics for Optical Lenses and Reflex Reflectors**

**Table of Contents**

<b>COVESTRO DEUTSCHLAND AG (EUROPE).....</b>	<b>9</b>
<b>COVESTRO LLC.....</b>	<b>9</b>
<b>COVESTRO (HONG KONG) LIMITED. ....</b>	<b>9</b>
<b>FORMOSA IDEMITSU PETROCHEMICAL CORP.....</b>	<b>13</b>
<b>LG CHEM, LTD .....</b>	<b>14</b>
<b>LOTTE CHEMICAL CORP.....</b>	<b>15</b>
<b>MITSUBISHI ENGINEERING PLASTICS CORP.....</b>	<b>18</b>
<b>MITSUBISHI GAS CHEMICAL (SHANGHAI) PLASTICS CORP., LTD.....</b>	<b>21</b>
<b>ROEHM AMERICA LLC.....</b>	<b>24</b>
<b>RÖHM GMBH.....</b>	<b>24</b>
<b>ROEHM CHEMICAL (SHANGHAI) CO., LTD.....</b>	<b>24</b>
<b>SABIC USA .....</b>	<b>25</b>
<b>SABIC BRAZIL.....</b>	<b>28</b>
<b>SABIC CHONGQING, CHINA.....</b>	<b>31</b>
<b>SABIC EUROPE.....</b>	<b>34</b>
<b>SABIC JAPAN.....</b>	<b>37</b>
<b>SABIC INDIA .....</b>	<b>40</b>
<b>SABIC KOREA.....</b>	<b>43</b>
<b>SABIC NANSHA, CHINA .....</b>	<b>46</b>
<b>SAM YANG CORPORATION.....</b>	<b>49</b>
<b>TEIJIN LIMITED .....</b>	<b>50</b>
<b>TEIJIN POLYCARBONATE CHINA LTD.....</b>	<b>52</b>
<b>TEIJIN POLYCARBONATE SINGAPORE PTE LTD.....</b>	<b>54</b>
<b>THAI POLYCARBONATE CO., LTD. ....</b>	<b>56</b>
<b>WANHUA CHEMICAL GROUP CO., LTD. ....</b>	<b>58</b>
<b>INDEX OF COMPANIES AND MATERIALS .....</b>	<b>59</b>
<b>APPENDIX A: AMECA ACCREDITED LABORATORY INFORMATION .....</b>	<b>62</b>
<b>APPENDIX B: FEDERAL STANDARD FOR PLASTICS .....</b>	<b>63</b>
<b>APPENDIX C: DOT INTERPRETATION FILES AND SUPPLEMENTAL LAB INFORMATION .....</b>	<b>68</b>

**Listing of Coating Suppliers**

**BASF Coatings GmbH, 9, 10, 25, 28, 31, 34, 37, 40, 43, 46**  
**Chugoku Marine Paints, Ltd., 10, 18, 21, 26, 29, 32, 35, 38, 41, 44, 47, 50, 52, 54, 56**  
**Fujikura Kasei Co., Ltd., 11, 18, 20, 21, 23, 26, 29, 32, 35, 38, 41, 44, 47, 50, 52, 54, 56, 57**  
**KCC Corporation, 11, 15, 17, 26, 29, 32, 35, 38, 41, 44, 47, 49, 51, 53, 55**  
**Mitsubishi Chemical Corporation, 10, 13, 15, 19, 22, 29, 32, 35, 38, 41, 44, 47, 51, 55, 57**  
**Momentive Performance Materials Inc., 11, 24, 27, 30, 33, 36, 39, 42, 45, 48, 51, 53, 55**  
**Red Spot Paint & Varnish Co., Inc., 11, 15, 27, 30, 33, 36, 39, 42, 45, 48, 58**  
**Shin-Etsu Chemical Co., Ltd., 27, 30, 33, 36, 39, 42, 45, 48**  
**Stanley Electric Co., Ltd., 12, 14, 19, 20, 22, 51, 53, 55, 57**

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Covestro Deutschland AG (Europe)  
 Covestro LLC (America)  
 Covestro (Hong Kong) Limited (Asia Pacific)  
[www.covestro.com](http://www.covestro.com)

MAKROLON AL2447	POLYCARBONATE	550012	Clear &
Makrolon® AL2447 MAS402		550396	Clear &
MAKROLON AL2447 RE		550660	Clear &
MAKROLON AL2447 RP(XX) CQ		550674	Clear &
MAKROLON AL2647		551013	Clear &
MAKROLON AL2647 RE		551019	Clear &
MAKROLON AL2647 RP(XX) CQ		551068	Clear &
(coated only)		551070	Clear &
		551104	Clear &
		550207	Clear &

Coated Covestro Deutschland AG (Europe), Covestro LLC (America) and Covestro (Hong Kong) Limited (Asia Pacific) Makrolon AL plastics may only be treated with the following acceptable coatings applied to the molded lens:

Note: Color 550674 are available on AL2647 only  
 Color 551013 is available on AL2447 only

#### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A, Acryking PH-930: See Mitsubishi Chemical Corporation

FUJIHARD HH2540U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

KUV-4000, KUV-5000, KUV-6000: See KCC Corporation

PHOLUCID 115C, PHOLUCID 130C and PHOLUCID 180C: See Chugoku Marine Paints

RayGloss 402: See BASF Coatings GmbH

SHP470FT/AS4700: See Momentive Performance Materials.

SH-61: See Stanley Electric Co., Ltd.

UVHC5000, UVHC5000K, and UVHC5000K1: See Momentive Performance Materials.

UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8: See Red Spot

(Coating information continued on the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------

**Coating Manufacturer in Alphabetical Order**

Information on RayGloss 402 coatings may be obtained by writing:



BASF Coatings GmbH  
 ECO/DT - C422  
 D-48165 Muenster  
 Germany  
[www.basf-coatings.com](http://www.basf-coatings.com)

Note: All Raygloss data submitted by BASF  
 Note: BASF RayGloss 402 were tested on 2447 and 2647 clear only



Information on PHOLUCID 115C, PHOLUCID 130C and PHOLUCID 180C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
 Tokyo Club Building,  
 2-6, Kasumigaseki 3-Chome  
 Chiyoda-Ku, Tokyo, 100-0013  
 Japan  
 Telephone: 81-3-3506-3971  
 Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: All PHOLUCID test data submitted by Chugoku Marine Paints.  
 Note: PHOLUCID 115C, PHOLUCID 130C was tested on Makrolon AL2447 and AL 2647 clear only.  
 Note: PHOLUCID 180C was tested on Makrolon AL 2447 clear only.



Information on Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A, and PH-930 coatings may be obtained by writing to the following company:

Mitsubishi Chemical Corporation  
 1-1 Marunouchi, 1-Chome  
 Chiyoda-Ku, Tokyo 100-8251  
 Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Note: All Covestro 5 year weathering data submitted by Mitsubishi Chemical Corporation  
 Note: Acryking PH-710 was tested on AL-2647 clear color only.  
 Note: Acryking PH-720 was tested on AL-2447 color 551070 only.  
 Note: Acryking PH-800, Acryking PH-800N5A and PH-930 was tested on AL-2447 and AL-2647 clear color only.

(Coating information continued on the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on KUV-4000, KUV-5000, KUV-6000 coatings may be obtained by writing:

KCC Corporation  
 83 Mabook-Dong, Giheung-Gu, Yongin-Si  
 Gyunggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

Note: All Covestro 5 year weathering data submitted by KCC Corporation  
 Note: KUV-4000, KUV-5000 was tested on AL2447 and AL2647 clear only.  
 Note: KUV-6000 was tested on AL2647 clear only



**FUJIKURA KASEI**

Information on FUJIHARD HH2540U and FUJIHARD HH3401U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
 6-15 Shibakeon 2-Chome  
 Minato-Ku, Tokyo, 105-0011  
 Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: All Covestro 5 year weathering data submitted by Fujikura Kasei Co., Ltd.  
 Note: FUJIHARD HH2540U and FUJIHARD HH3401U was tested on AL2447 and AL2647 clear only.



Information on SHP470FT/AS4700, UVHC5000, UVHC5000K, and UVHC5000K1 hard coat may be obtained by writing to the following address:

Momentive Performance Materials GmbH Building V7 51368 Lverkusen Germany	Momentive Performance Materials Inc. 260 Hudson River Road Waterford, NY 12118 <a href="http://www.momentive.com">www.momentive.com</a>
---	--

Note: All Covestro 5 year weathering data submitted by Momentive Performance Materials except for Makrolon® AL2447 MAS402.  
 Note: UVHC5000 was tested on AL2447, Makrolon® AL2447 MAS402, and AL2647 clear only.  
 Note: SHP470FT/AS4700 was tested on AL2447 clear only.



**PAINT & VARNISH COMPANY, INC.**

Information on UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 coatings may be obtained by writing to the following address:

Red Spot Paint & Varnish Co., Inc.  
 P.O. Box 418  
 Evansville, IN 47703-0418  
[www.redspot.com](http://www.redspot.com)

Note: All Covestro 5 year weathering data submitted by Red Spot Paint & Varnish Co., Inc.  
 Note: UVT820 series coatings were tested on AL2447 clear only

(Coating information continued on the next page.)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------

Information on Stanley Electric SH-61 may be obtained by writing to the following company:



Stanley Electric Co., Ltd.  
2-9-13, Nakameguro,  
Meguro-Ku, Tokyo 153  
Japan  
[www.stanley.co.jp](http://www.stanley.co.jp)

Note: All 5 year data submitted by Stanley Electric Co., Ltd.  
Note: SH-61 was tested on Covestro AL2447

---

---

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
Formosa Idemitsu Petrochemical Corp.	TARFLON IV1900R TARFLON IV2200R (coated applications only)	Polycarbonate		Clear &

[www.ipc.idemitsu.co.jp](http://www.ipc.idemitsu.co.jp)

Coated Formosa Idemitsu Petrochemical Corp. plastics may only be used when treated with the following acceptable coating applied to the molded lens:

#### **Coating in Alphabetical Order and Corresponding Manufacturer**

Acryking PH-800 and Acryking PH-800N5A: See Mitsubishi Chemical Corporation

#### **Coating Manufacturer in Alphabetical Order**



**MITSUBISHI  
CHEMICAL  
GROUP**

Information on Acryking PH-800 and Acryking PH-800N5A coatings may be obtained by writing to the following company:

Mitsubishi Chemical Corporation  
1-1 Marunouchi, 1-Chome  
Chiyoda-Ku, Tokyo 100-8251  
Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------

LG Chem, Ltd.	PC1303AH-22 W10T (coated applications only)	Polycarbonate		Clear &
---------------	--	---------------	--	---------

[www.lgchem.com](http://www.lgchem.com)

Coated LG Chem Ltd. plastics are listed with only the following coatings applied to the molded lens:

#### **Coating in Alphabetical Order and Corresponding Manufacturer**

SH-K142, and SH-K151: See Stanley Electric

#### **Coating Manufacturer in Alphabetical Order**

Information on Stanley Electric SH-K142, and SH-K151, may be obtained by writing to the following company:



Stanley Electric Co., Ltd.  
2-9-13, Nakameguro,  
Meguro-Ku, Tokyo 153  
Japan  
[www.stanley.co.jp](http://www.stanley.co.jp)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
Lotte Chemical Corp. <a href="http://www.lottechem.com">www.lottechem.com</a>	LT-1100 LT-1220 (Coated Only)	Polycarbonate		Clear &

Coated Lotte Chemical Corp. plastics are only acceptable with the coatings listed below when properly applied to the molded lens.

### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-800 and Acryking PH-800N5A: See Mitsubishi Chemical Corporation

KUV 5000: See KCC Corporation

UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8: See Red Spot

### Coating Manufacturer in Alphabetical Order



Information on KUV-5000 coating may be obtained by writing:

KCC Corporation  
83 Mabook-Dong, Giheung-Gu, Yongin-Si  
Gyeonggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

Note: KUV-5000 was tested on LT-1220 clear only.



Information on Acryking PH-800 and Acryking PH-800N5A coatings may be obtained by writing to the following company:

Mitsubishi Chemical Corporation  
1-1 Marunouchi, 1-Chome  
Chiyoda-Ku, Tokyo 100-8251  
Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Note: Lotte Chemical Corp. plastics are only to be used in a production process approved and monitored by Mitsubishi Chemical Corporation



Information on UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 coatings may be obtained by writing to the following address:

Red Spot Paint & Varnish Co., Inc.  
P.O. Box 418  
Evansville, IN 47703-0418  
[www.redspot.com](http://www.redspot.com)

<b><u>MFR.</u></b>	<b><u>TRADE NAME and FLOW FORMULATION</u></b>	<b><u>TYPE OF RESIN</u></b>	<b><u>NUMBER</u></b>	<b><u>COLOR</u></b>
--------------------	---	-----------------------------	----------------------	---------------------

Note: UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 was tested on LT-1100 and LT-1220 Clear

---

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
Lotte Chemical Corp.	PC-1000L (Coated Only)	Polycarbonate		Clear &

[www.lottechem.com](http://www.lottechem.com)

Coated Lotte Chemical Corp. plastics are only acceptable with the coatings listed below when properly applied to the molded lens.

#### **Coating in Alphabetical Order and Corresponding Manufacturer**

KUV-5000: See KCC Corporation

#### **Coating Manufacturer in Alphabetical Order**



Information on KUV-5000 coating may be obtained by writing:

KCC Corporation  
 83 Mabook-Dong, Giheung-Gu, Yongin-Si  
 Gyunggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

Note: KUV-5000 was tested on PC-1000L clear only.

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
Mitsubishi Engineering Plastics Corp.	IUPIILON ML-300 IUPIILON ML-300AH (Coated Only)	POLYCARBONATE	001	Clear &

[www.m-ep.co.jp](http://www.m-ep.co.jp)

Coated Mitsubishi Engineering Plastics Corp. Iupilon plastics may only be treated with the following coatings listed below.

#### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930: See Mitsubishi Chemical Corporation

FUJIHARD HH2540U, FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

PHOLUCID 180C and 185C: See Chugoku Marine Paints, Ltd.

SH-61: See Stanley Electric Co., Ltd.

#### Coating Manufacturer in Alphabetical Order



Information on PHOLUCID 180C and 185C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
Tokyo Club Building,  
2-6, Kasumigaseki 3-Chome  
Chiyoda-Ku, Tokyo, 100-0013  
Japan  
Telephone: 81-3-3506-3971  
Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: PHOLUCID 180C and 185C was tested on Clear IUPIILON ML-300AH only.



Information on FUJIHARD HH2540U, FUJIHARD HH3372U and FUJIHARD HH3401U coatings may be obtained by writing  
Fujikura Kasei Co., Ltd.  
6-15 Shibakeon 2-Chome  
Minato-Ku, Tokyo, 105-0011  
Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH3401U was tested on Clear IUPIILON ML-300 and IUPIILON ML-350 only

(Coating information continued on the next page.)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings may be obtained by writing to the following company:

Mitsubishi Chemical Corporation  
1-1 Marunouchi, 1-Chome  
Chiyoda-Ku, Tokyo 100-8251 Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Information on Stanley Electric SH-61 may be obtained by writing to the following company:



Stanley Electric Co., Ltd.  
2-9-13, Nakameguro,  
Meguro-Ku, Tokyo 153  
Japan  
[www.stanley.co.jp](http://www.stanley.co.jp)

Note: SH-61 was tested on ML-300

---

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------

Information on Stanley Electric SH-61 may be obtained by writing to the following company:



Stanley Electric Co., Ltd.  
2-9-13, Nakameguro,  
Meguro-Ku, Tokyo 153  
Japan  
[www.stanley.co.jp](http://www.stanley.co.jp)

Note: All 5 year data submitted by Stanley Electric Co., Ltd.  
Note: SH-61 was tested on Covestro AL2447

Mitsubishi Engineering Plastics Corp.	IUPILON ML-350 (Coated Only)	POLYCARBONATE	001	Clear &
---------------------------------------	------------------------------	---------------	-----	---------

[www.m-ep.co.jp](http://www.m-ep.co.jp)

Coated Mitsubishi Engineering Plastics Corp. Iupilon ML-350 plastics may only be treated with the following coatings listed below.

#### Coating in Alphabetical Order and Corresponding Manufacturer

FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

#### Coating Manufacturer in Alphabetical Order



Information on FUJIHARD HH3372U and FUJIHARD HH3401U coating may be obtained by writing:

Fujikura Kasei Co., Ltd.  
6-15 Shibakeon 2-Chome  
Minato-Ku, Tokyo, 105-0011  
Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH3401U was tested on Clear IUPILON ML-300 and IUPILON ML-350 only

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
Mitsubishi Gas Chemical Engineering-Plastics (Shanghai) Co. Ltd.	IUPILON ML-300 IUPILON ML-300AH (Coated Only)	POLYCARBONATE	001	Clear &

[www.m-ep.co.jp](http://www.m-ep.co.jp)

Coated Mitsubishi Gas Chemical Engineering Plastics (Shanghai) Co. Ltd. Iupilon ML-300 plastics may only be treated with the following coatings listed below.

#### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930: See Mitsubishi Chemical Corporation

FUJIHARD HH2540U, FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

PHOLUCID 180C and PHOLUCID 185C: See Chugoku Marine Paints, Ltd.

SH-60: See Stanley Electric Co., Ltd.

#### Coating Manufacturer in Alphabetical Order



Information on PHOLUCID 180C and PHOLUCID 185C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
Tokyo Club Building,  
2-6, Kasumigaseki 3-Chome  
Chiyoda-Ku, Tokyo, 100-0013  
Japan  
Telephone: 81-3-3506-3971  
Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: PHOLUCID 180C and PHOLUCID 185C was tested on Clear IUPILON ML-300AH only.



Information on FUJIHARD HH2540U and FUJIHARD HH3372U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
6-15 Shibakeon 2-Chome  
Minato-Ku, Tokyo, 105-0011  
Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH3401U was tested on clear IUPILON ML-300 and ML-350 only  
(Coating information continued on the next page.)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



MITSUBISHI  
CHEMICAL  
GROUP

Information on Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings may be obtained by writing to the following company:

Mitsubishi Chemical Corporation  
1-1 Marunouchi, 1-Chome  
Chiyoda-Ku, Tokyo 100-8251  
Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Information on Stanley Electric SH-61 may be obtained by writing to the following company:



Stanley Electric Co., Ltd.  
2-9-13, Nakameguro,  
Meguro-Ku, Tokyo 153  
Japan  
[www.stanley.co.jp](http://www.stanley.co.jp)

Note: SH-61 was tested on ML-300

---

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
Mitsubishi Gas Chemical Engineering-Plastics (Shanghai) Co. Ltd. <a href="http://www.m-ep.co.jp">www.m-ep.co.jp</a>	IUPILON ML-350 (Coated Only)	POLYCARBONATE	001	Clear &

Coated Mitsubishi Gas Chemical Engineering Plastics (Shanghai) Co. Ltd. Iupilon ML-350 plastics may only be treated with the following coatings listed below.

#### Coating in Alphabetical Order and Corresponding Manufacturer

FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

#### Coating Manufacturer in Alphabetical Order



Information on FUJIHARD HH3372U and FUJIHARD HH3401U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
6-15 Shibakeon 2-Chome  
Minato-Ku, Tokyo, 105-0011  
Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH3401U was tested on Clear IUPILON ML-300 and IUPILON ML-350 only

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------

**RÖHM**

TRADITIONALLY  
INNOVATIVE

Roehm America LLC	PLEXIGLAS® Resist AG100	Polymethyl		Clear
Röhm GmbH	PLEXIGLAS® Resist AG100 L02	Methacrylate	9V913	Clear
Roehm Chemical. (Shanghai) Co., Ltd	ACRYLITE® Resist AG100			
	ACRYLITE® Resist AG100 L02			

[www.acrylite-polymers.com](http://www.acrylite-polymers.com)

[www.roehm.com](http://www.roehm.com)

[www.Plexiglas.de](http://www.Plexiglas.de)

Note: Röhm 5 year materials *do not* need to be coated unless used as a réflex reflector or in front of a réflex reflector in thickness above 6.4mm

Note: Röhm 5 year materials over 6.4mm and used as a réflex reflector or in front of a réflex reflector are only listed as coated with PHC XH100P

### Coating in Alphabetical Order and Corresponding Manufacturer

PHC XH100P: See Momentive Performance Materials.

### Coating Manufacturer in Alphabetical Order

Information on PHC XH100P hard coat may be obtained by writing to the following address:

Momentive Performance Materials GmbH  
Building V7  
51368 Lverkusen  
Germany

Momentive Performance Materials Inc.  
260 Hudson River Road  
Waterford, NY 12118  
[www.momentive.com](http://www.momentive.com)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
	SABIC LEXAN® LS1	POLYCARBONATE	111	White &
	USA LEXAN® LS2 (Coated Only)		111S	White &
	<a href="http://www.sabic.com">www.sabic.com</a>			

Coated SABIC USA plastics may only be treated with the following acceptable coatings applied to the molded lens:

#### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-710, Acryking PH-720, Acryking PH-800 Acryking PH-800N5A and Acryking PH-930 coatings: See Mitsubishi Chemical Corporation

FUJIHARD HH2540U, FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

KUV-5000, KUV-6000, and KUV-9100: See KCC Corporation

RayGloss 402: See BASF Coatings GmbH

UVHC5000, UVHC5000K, and UVHC5000K1: See Momentive Performance Materials.

UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8: See Red Spot

PHOLUCID 130C: See Chugoku Marine Paints

X-48-5500-A18: See Shin-Etsu Chemical Co., Ltd.

#### Coating Manufacturer in Alphabetical Order

Information on RayGloss 402 coatings may be obtained by writing:



BASF Coatings GmbH  
 ECO/DT - C422  
 D-48165 Muenster  
 Germany  
[www.basf-coatings.com](http://www.basf-coatings.com)

Note: BASF RayGloss 402 were tested on LS1 and LS2 clear only

(Coating information continued the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on PHOLUCID 130C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
 Tokyo Club Building,  
 2-6, Kasumigaseki 3-Chome  
 Chiyoda-Ku, Tokyo, 100-0013  
 Japan  
 Telephone: 81-3-3506-3971  
 Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: PHOLUCID 130C was tested on Sabic LS1 clear only.



**FUJIKURA KASEI**

Information on FUJIHARD HH2540U, FUJIHARD HH3372U and FUJIHARD HH3401U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
 6-15 Shibakeon 2-Chome  
 Minato-Ku, Tokyo, 105-0011  
 Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH2540U was tested on LS2 111S Clear Only.

Note: FUJIHARD HH3372U and FUJIHARD HH3401U were tested on LS1-111 and LS2-111 Clear Only.



Information on KUV-5000, KUV-6000 and KUV-9100 coatings may be obtained by writing:

KCC Corporation  
 83 Mabook-Dong, Giheung-Gu, Yongin-Si  
 Gyunggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

Note: KUV-5000 and KUV-9100 was tested on SABIC LS1-111 and SABIC LS2-111 clear only.



**MITSUBISHI  
 CHEMICAL  
 GROUP**

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A, Acryking PH-930 coatings may be obtained by writing to the following address:

Mitsubishi Chemical Corporation  
 1-1 Marunouchi, 1-Chome  
 Chiyoda-Ku, Tokyo 100-8251  
 Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Note: Acryking PH-710, Acryking PH-720 and Acryking PH-800 was tested on SABIC LS1-111 only.  
 Acryking PH-720, Acryking PH-800 and Acryking PH-800N5A was tested on SABIC LS2-111 only.  
 Acryking PH-930 was tested on SABIC LS1 and LS2 clear only

(Coating information continued the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on UVHC5000, UVHC5000K, and UVHC5000K1 hard coat may be obtained by writing to the following address:

Momentive Performance Materials GmbH  
 Building V7  
 51368 Lverkusen  
 Germany

Momentive Performance Materials Inc.  
 260 Hudson River Road  
 Waterford, NY 12118  
[www.momentive.com](http://www.momentive.com)

Note: UVHC5000 was tested on SABIC LS1 and LS2 clear only.



PAINT & VARNISH COMPANY, INC.

Information on UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 coatings may be obtained by writing to the following address:

Red Spot Paint & Varnish Co., Inc.  
 P.O. Box 418  
 Evansville, IN 47703-0418  
[www.redspot.com](http://www.redspot.com)

Note: UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 was tested on LS1-111/LS2-111 Clear only



Information of X-48-5500-A18 hard coat may be obtained by writing to the following address:

Shin-Etsu Chemical Co., Ltd.  
 4-1, Marunouchi 1-Chome  
 Chiyoda-ku, Tokyo 100-0005,  
 Japan  
[www.shinetsu.co.jp](http://www.shinetsu.co.jp)

Note: X-48-5500-A18 was tested on SABIC LS1-111, 111J and 111H clear only.

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------

	SABIC	LEXAN® LS1	POLYCARBONATE	111	White &
	Brazil	LEXAN® LS2 (Coated Only)		111S	White &
<a href="http://www.sabic.com">www.sabic.com</a>					

Coated SABIC Brazil plastics may only be treated with the following acceptable coatings applied to the molded lens:

#### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings: See Mitsubishi Chemical Corporation

FUJIHARD HH2540U, FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

KUV-5000, KUV-6000, and KUV-9100: See KCC Corporation

RayGloss 402: See BASF Coatings GmbH

UVHC5000, UVHC5000K, and UVHC5000K1: See Momentive Performance Materials.

UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8: See Red Spot

PHOLUCID 130C: See Chugoku Marine Paints

X-48-5500-A18: See Shin-Etsu Chemical Co., Ltd.

#### Coating Manufacturer in Alphabetical Order

Information on RayGloss 402 coatings may be obtained by writing:



BASF Coatings GmbH  
 ECO/DT - C422  
 D-48165 Muenster  
 Germany  
[www.basf-coatings.com](http://www.basf-coatings.com)

Note: BASF RayGloss 402 were tested on LS1 and LS2 clear only

(Coating information continued the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on PHOLUCID 130C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
Tokyo Club Building,  
2-6, Kasumigaseki 3-Chome  
Chiyoda-Ku, Tokyo, 100-0013  
Japan  
Telephone: 81-3-3506-3971  
Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: PHOLUCID 130C was tested on Sabc LS1 clear only.



**FUJIKURA KASEI**

Information on FUJIHARD HH2540U, FUJIHARD HH3372U and FUJIHARD HH3401U coatings may be obtained by writing

Fujikura Kasei Co., Ltd.  
6-15 Shibakeon 2-Chome  
Minato-Ku, Tokyo, 105-0011  
Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH2540U was tested on LS2 111S Clear Only.

Note: FUJIHARD HH3372U and FUJIHARD HH3401U were tested on LS1-111 and LS2-111 Clear Only.



Information on KUV-5000, KUV-6000 and KUV-9100 coatings may be obtained by writing:

KCC Corporation  
83 Mabook-Dong, Giheung-Gu, Yongin-Si  
Gyunggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

Note: KUV-5000 and KUV-9100 was tested on SABIC LS1-111 and SABIC LS2-111 clear only.



Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A, and Acryking PH-930 coatings may be obtained by writing to the following address:

Mitsubishi Chemical Corporation  
1-1 Marunouchi, 1-Chome  
Chiyoda-Ku, Tokyo 100-8251  
Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Note: Acryking PH-710, Acryking PH-720 and Acryking PH-800 was tested on SABIC LS1-111 only.  
Acryking PH-720 Acryking PH-800 and Acryking PH-800N5A was tested on SABIC LS2-111 only.  
Acryking PH-930 was tested on SABIC LS1 and LS2 clear only

(Coating information continued the next page)

**MFR.**                      **TRADE NAME and**  
**FLOW FORMULATION**                      **TYPE OF RESIN**                      **NUMBER**                      **COLOR**



Information on UVHC5000, UVHC5000K, and UVHC5000K1 hard coat may be obtained by writing to the following address:

Momentive Performance Materials GmbH  
Building V7  
51368 Lverkusen  
Germany

Momentive Performance Materials Inc.  
260 Hudson River Road  
Waterford, NY 12118  
[www.momentive.com](http://www.momentive.com)

Note: UVHC5000 was tested on SABIC LS1 and LS2 clear only.



PAINT & VARNISH COMPANY, INC.

Information on UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 coatings may be obtained by writing to the following address:

Red Spot Paint & Varnish Co., Inc.  
P.O. Box 418  
Evansville, IN 47703-0418  
[www.redspot.com](http://www.redspot.com)

Note: UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 was tested on LS1-111/LS2-111 Clear only



Information of X-48-5500-A18 hard coat may be obtained by writing to the following address:

Shin-Etsu Chemical Co., Ltd.  
4-1, Marunouchi 1-Chome  
Chiyoda-ku, Tokyo 100-0005,  
Japan  
[www.shinetsu.co.jp](http://www.shinetsu.co.jp)

Note: X-48-5500-A18 was tested on SABIC LS1-111, 111J and 111H clear only.

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
	SABIC LEXAN® LS1	POLYCARBONATE	111	White &
	Chongqing LEXAN® LS2		111HX	White &
	China (Coated Only)		111H	White &
	<a href="http://www.sabic.com">www.sabic.com</a>			

Coated SABIC Chongqing, China plastics may only be treated with the following acceptable coatings applied to the molded lens:

#### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings: See Mitsubishi Chemical Corporation

FUJIHARD HH2540U, FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

KUV-5000, KUV-6000, and KUV-9100: See KCC Corporation

UVHC5000, UVHC5000K, and UVHC5000K1: See Momentive Performance Materials.

UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8: See Red Spot

PHOLUCID 130C: See Chugoku Marine Paints

X-48-5500-A18: See Shin-Etsu Chemical Co., Ltd.

#### Coating Manufacturer in Alphabetical Order



Information on RayGloss 402 coatings may be obtained by writing:

BASF Coatings GmbH  
 ECO/DT - C422  
 D-48165 Muenster  
 Germany  
[www.basf-coatings.com](http://www.basf-coatings.com)

Note: BASF RayGloss 402 were tested on LS1 and LS2 clear only

(Coating information continued the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on PHOLUCID 130C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
Tokyo Club Building,  
2-6, Kasumigaseki 3-Chome  
Chiyoda-Ku, Tokyo, 100-0013  
Japan  
Telephone: 81-3-3506-3971  
Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: PHOLUCID 130C was tested on Sabic LS1 clear only.



**FUJIKURA KASEI**

Information on FUJIHARD HH2540U, FUJIHARD HH3372U and FUJIHARD HH3401U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
6-15 Shibakeon 2-Chome  
Minato-Ku, Tokyo, 105-0011  
Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH2540U was tested on LS2 111S Clear Only.

Note: FUJIHARD HH3372U and FUJIHARD HH3401U were tested on LS1-111 and LS2-111 Clear Only.



Information on KUV-5000, KUV-6000 and KUV-9100 coatings may be obtained by writing:

KCC Corporation  
83 Mabook-Dong, Giheung-Gu, Yongin-Si  
Gyunggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

Note: KUV-5000 and KUV-9100 was tested on SABIC LS1-111 and SABIC LS2-111 clear only.



Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings may be obtained by writing to the following address:

Mitsubishi Chemical Corporation  
1-1 Marunouchi, 1-Chome  
Chiyoda-Ku, Tokyo 100-8251  
Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Note: Acryking PH-710, Acryking PH-720 and Acryking PH-800 was tested on SABIC LS1-111 only.

Acryking PH-720 and PH-800 was tested on SABIC LS2-111 only.

Acryking PH-930 was tested on SABIC LS1 and LS2 clear only

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on UVHC5000, UVHC5000K, and UVHC5000K1 hard coat may be obtained by writing to the following address:

Momentive Performance Materials GmbH  
 Building V7  
 51368 Lverkusen  
 Germany

Momentive Performance Materials Inc.  
 260 Hudson River Road  
 Waterford, NY 12118  
[www.momentive.com](http://www.momentive.com)

Note: UVHC5000 was tested on SABIC LS1 and LS2 clear only.



PAINT & VARNISH COMPANY, INC.

Information on UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 coatings may be obtained by writing to the following address:

Red Spot Paint & Varnish Co., Inc.  
 P.O. Box 418  
 Evansville, IN 47703-0418  
[www.redspot.com](http://www.redspot.com)

Note: UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 was tested on LS1-111/LS2-111 Clear only



Information of X-48-5500-A18 hard coat may be obtained by writing to the following address:

Shin-Etsu Chemical Co., Ltd.  
 4-1, Marunouchi 1-Chome  
 Chiyoda-ku, Tokyo 100-0005,  
 Japan  
[www.shinetsu.co.jp](http://www.shinetsu.co.jp)

Note: X-48-5500-A18 was tested on SABIC LS1-111, 111J and 111H clear only.

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



SABIC Europe	LEXAN® LS1 LEXAN® LS2 (Coated Only)	POLYCARBONATE	111 111H 111HX	White & White & White &
--------------	---	---------------	----------------------	-------------------------------

[www.sabic.com](http://www.sabic.com)

Coated SABIC Europe plastics may only be treated with the following acceptable coatings applied to the molded lens:

#### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings: See Mitsubishi Chemical Corporation

FUJIHARD HH2540U, FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

KUV-5000, KUV-6000 and KUV-9100: See KCC Corporation

RayGloss 402: See BASF Coatings GmbH

UVHC5000, UVHC5000K, and UVHC5000K1: See Momentive Performance Materials.

UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8: See Red Spot

PHOLUCID 130C: See Chugoku Marine Paints

X-48-5500-A18: See Shin-Etsu Chemical Co., Ltd.

#### Coating Manufacturer in Alphabetical Order

Information on RayGloss 402 coatings may be obtained by writing:



BASF Coatings GmbH  
ECO/DT - C422  
D-48165 Muenster  
Germany  
[www.basf-coatings.com](http://www.basf-coatings.com)

Note: BASF RayGloss 402 were tested on LS1 and LS2 clear only

(Coating information continued the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on PHOLUCID 130C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
 Tokyo Club Building,  
 2-6, Kasumigaseki 3-Chome  
 Chiyoda-Ku, Tokyo, 100-0013  
 Japan  
 Telephone: 81-3-3506-3971  
 Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: PHOLUCID 130C was tested on Sabc LS1 clear only.



Information on KUV-5000, KUV-6000 and KUV-9100 coatings may be obtained by writing:

KCC Corporation  
 83 Mabook-Dong, Giheung-Gu, Yongin-Si  
 Gyunggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

Note: KUV-5000 and KUV-9100 was tested on SABIC LS1-111 and SABIC LS2-111 clear only.



**FUJIKURA KASEI**

Information on FUJIHARD HH2540U, FUJIHARD HH3372U and FUJIHARD HH3401U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
 6-15 Shibakeon 2-Chome  
 Minato-Ku, Tokyo, 105-0011  
 Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH2540U was tested on LS2 111S Clear Only.

Note: FUJIHARD HH3372U and FUJIHARD HH3401U were tested on LS1-111 and LS2-111 Clear Only.



**MITSUBISHI  
 CHEMICAL  
 GROUP**

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings may be obtained by writing to the following address:

Mitsubishi Chemical Corporation  
 1-1 Marunouchi, 1-Chome  
 Chiyoda-Ku, Tokyo 100-8251  
 Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Note: Acryking PH-710, Acryking PH-720 and Acryking PH-800 was tested on SABIC LS1-111 only.

Acryking PH-720 and PH-800 was tested on SABIC LS2-111 only.

Acryking PH-930 was tested on SABIC LS1 and LS2 clear only

(Coating information continued the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on UVHC5000, UVHC5000K, and UVHC5000K1 hard coat may be obtained by writing to the following address:

Momentive Performance Materials GmbH  
 Building V7  
 51368 Lverkusen  
 Germany

Momentive Performance Materials Inc.  
 260 Hudson River Road  
 Waterford, NY 12118  
[www.momentive.com](http://www.momentive.com)

Note: UVHC5000 was tested on SABIC LS1 and LS2 clear only.



PAINT & VARNISH COMPANY, INC.

Information on UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 coatings may be obtained by writing to the following address:

Red Spot Paint & Varnish Co., Inc.  
 P.O. Box 418  
 Evansville, IN 47703-0418  
[www.redspot.com](http://www.redspot.com)

Note: UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 was tested on LS1-111/LS2-111 Clear only



Information of X-48-5500-A18 hard coat may be obtained by writing to the following address:

Shin-Etsu Chemical Co., Ltd.  
 4-1, Marunouchi 1-Chome  
 Chiyoda-ku, Tokyo 100-0005,  
 Japan  
[www.shinetsu.co.jp](http://www.shinetsu.co.jp)

Note: X-48-5500-A18 was tested on SABIC LS1-111, 111J and 111H clear only.

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
	SABIC LEXAN® LS1	POLYCARBONATE	111	White &
	Japan LEXAN® LS2 (Coated Only)		111S	White &
	<a href="http://www.sabic.com">www.sabic.com</a>			

Coated SABIC Japan plastics may only be treated with the following acceptable coatings applied to the molded lens:

#### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings: See Mitsubishi Chemical Corporation

FUJIHARD HH2540U, FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

KUV-5000, KUV-6000, and KUV-9100: See KCC Corporation

RayGloss 402: See BASF Coatings GmbH

UVHC5000, UVHC5000K, and UVHC5000K1: See Momentive Performance Materials.

UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8: See Red Spot

PHOLUCID 130C: See Chugoku Marine Paints

X-48-5500-A18: See Shin-Etsu Chemical Co., Ltd.

#### Coating Manufacturer in Alphabetical Order



Information on RayGloss 402 coatings may be obtained by writing:

BASF Coatings GmbH  
 ECO/DT - C422  
 D-48165 Muenster  
 Germany  
[www.basf-coatings.com](http://www.basf-coatings.com)

Note: BASF RayGloss 402 were tested on LS1 and LS2 clear only

(Coating information continued the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on PHOLUCID 130C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
 Tokyo Club Building,  
 2-6, Kasumigaseki 3-Chome  
 Chiyoda-Ku, Tokyo, 100-0013  
 Japan  
 Telephone: 81-3-3506-3971  
 Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: PHOLUCID 130C was tested on Sabc LS1 clear only.



Information on KUV-5000, KUV-6000 and KUV-9100 coatings may be obtained by writing:

KCC Corporation  
 83 Mabook-Dong, Giheung-Gu, Yongin-Si  
 Gyunggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

Note: KUV-5000 and KUV-9100 was tested on SABIC LS1-111 and SABIC LS2-111 clear only.



**FUJIKURA KASEI**

Information on FUJIHARD HH2540U, FUJIHARD HH3372U and FUJIHARD HH3401U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
 6-15 Shibakeon 2-Chome  
 Minato-Ku, Tokyo, 105-0011  
 Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH2540U was tested on LS2 111S Clear Only.

Note: FUJIHARD HH3372U and FUJIHARD HH3401U were tested on LS1-111 and LS2-111 Clear Only.



**MITSUBISHI  
 CHEMICAL  
 GROUP**

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings may be obtained by writing to the following address:

Mitsubishi Chemical Corporation  
 1-1 Marunouchi, 1-Chome  
 Chiyoda-Ku, Tokyo 100-8251  
 Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Note: Acryking PH-710, Acryking PH-720 and Acryking PH-800 was tested on SABIC LS1-111 only.

Acryking PH-720 and PH-800 was tested on SABIC LS2-111 only.

Acryking PH-930 was tested on SABIC LS1 and LS2 clear only

(Coating information continued the next page)

**MFR.**                      **TRADE NAME and**  
**FLOW FORMULATION**                      **TYPE OF RESIN**                      **NUMBER**                      **COLOR**



Information on UVHC5000, UVHC5000K, and UVHC5000K1 hard coat may be obtained by writing to the following address:

Momentive Performance Materials GmbH  
Building V7  
51368 Lverkusen  
Germany

Momentive Performance Materials Inc.  
260 Hudson River Road  
Waterford, NY 12118  
[www.momentive.com](http://www.momentive.com)

Note: UVHC5000 was tested on SABIC LS1 and LS2 clear only.



PAINT & VARNISH COMPANY, INC.

Information on UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 coatings may be obtained by writing to the following address:

Red Spot Paint & Varnish Co., Inc.  
P.O. Box 418  
Evansville, IN 47703-0418  
[www.redspot.com](http://www.redspot.com)

Note: UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 was tested on LS1-111/LS2-111 Clear only



Information of X-48-5500-A18 hard coat may be obtained by writing to the following address:

Shin-Etsu Chemical Co., Ltd.  
4-1, Marunouchi 1-Chome  
Chiyoda-ku, Tokyo 100-0005,  
Japan  
[www.shinetsu.co.jp](http://www.shinetsu.co.jp)

Note: X-48-5500-A18 was tested on SABIC LS1-111, 111J and 111H clear only.

---

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



SABIC India  
 LEXAN® LS1  
 LEXAN® LS2  
 (Coated Only)

POLYCARBONATE

111

White &

[www.sabic.com](http://www.sabic.com)

Coated SABIC India plastics may only be treated with the following acceptable coatings applied to the molded lens:

**Coating in Alphabetical Order and Corresponding Manufacturer**

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings: See Mitsubishi Chemical Corporation

FUJIHARD HH2540U, FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

KUV-5000, KUV-6000 and KUV-9100: See KCC Corporation

RayGloss 402: See BASF Coatings GmbH

UVHC5000, UVHC5000K, and UVHC5000K1: See Momentive Performance Materials.

UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8: See Red Spot

PHOLUCID 130C: See Chugoku Marine Paints

X-48-5500-A18: See Shin-Etsu Chemical Co., Ltd.

**Coating Manufacturer in Alphabetical Order**

Information on RayGloss 402 coatings may be obtained by writing:



BASF Coatings GmbH  
 ECO/DT - C422  
 D-48165 Muenster  
 Germany

[www.basf-coatings.com](http://www.basf-coatings.com)

Note: BASF RayGloss 402 were tested on LS1 and LS2 clear only

(Coating information continued the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on PHOLUCID 130C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
 Tokyo Club Building,  
 2-6, Kasumigaseki 3-Chome  
 Chiyoda-Ku, Tokyo, 100-0013  
 Japan  
 Telephone: 81-3-3506-3971  
 Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: PHOLUCID 130C was tested on Sabic LS1 clear only.



Information on KUV-5000, KUV-6000 and KUV-9100 coatings may be obtained by writing:

KCC Corporation  
 83 Mabook-Dong, Giheung-Gu, Yongin-Si  
 Gyunggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

Note: KUV-5000 and KUV-9100 was tested on SABIC LS1-111 and SABIC LS2-111 clear only.



**FUJIKURA KASEI**

Information on FUJIHARD HH2540U, FUJIHARD HH3372U, and FUJIHARD HH3401U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
 6-15 Shibakeon 2-Chome  
 Minato-Ku, Tokyo, 105-0011  
 Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH2540U was tested on LS2 111S Clear Only.

Note: FUJIHARD HH3372U and FUJIHARD HH3401U were tested on LS1-111 and LS2-111 Clear Only.



Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings may be obtained by writing to the following address:

Mitsubishi Chemical Corporation  
 1-1 Marunouchi, 1-Chome  
 Chiyoda-Ku, Tokyo 100-8251  
 Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Note: Acryking PH-710, Acryking PH-720 and Acryking PH-800 was tested on SABIC LS1-111 only.  
 Acryking PH-720 and PH-800 was tested on SABIC LS2-111 only.  
 Acryking PH-930 was tested on SABIC LS1 and LS2 clear only

(Coating information continued on the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on UVHC5000, UVHC5000K, and UVHC5000K1 hard coat may be obtained by writing to the following address:

Momentive Performance Materials GmbH  
Building V7  
51368 Lverkusen  
Germany

Momentive Performance Materials Inc.  
260 Hudson River Road  
Waterford, NY 12118  
[www.momentive.com](http://www.momentive.com)

Note: UVHC5000 was tested on SABIC LS1 and LS2 clear only.



PAINT & VARNISH COMPANY, INC.

Information on UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 coatings may be obtained by writing to the following address:

Red Spot Paint & Varnish Co., Inc.  
P.O. Box 418  
Evansville, IN 47703-0418  
[www.redspot.com](http://www.redspot.com)

Note: UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 was tested on LS1-111/LS2-111 Clear only



Information of X-48-5500-A18 hard coat may be obtained by writing to the following address:

Shin-Etsu Chemical Co., Ltd.  
4-1, Marunouchi 1-Chome  
Chiyoda-ku, Tokyo 100-0005,  
Japan  
[www.shinetsu.co.jp](http://www.shinetsu.co.jp)

Note: X-48-5500-A18 was tested on SABIC LS1-111, 111J and 111H clear only.

---

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
	SABIC LEXAN® LS1	POLYCARBONATE	111	White &
	Korea LEXAN® LS2 (Coated Only)		111S	White &
	<a href="http://www.sabic.com">www.sabic.com</a>			

Coated SABIC Korea plastics may only be treated with the following acceptable coatings applied to the molded lens:

#### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings: See Mitsubishi Chemical Corporation

FUJIHARD HH2540U, FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

KUV-5000, KUV-6000 and KUV-9100: See KCC Corporation

RayGloss 402: See BASF Coatings GmbH

UVHC5000, UVHC5000K, and UVHC5000K1: See Momentive Performance Materials.

UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8: See Red Spot

PHOLUCID 130C: See Chugoku Marine Paints

X-48-5500-A18: See Shin-Etsu Chemical Co., Ltd.

#### Coating Manufacturer in Alphabetical Order



Information on RayGloss 402 coatings may be obtained by writing:

BASF Coatings GmbH  
 ECO/DT - C422  
 D-48165 Muenster  
 Germany  
[www.basf-coatings.com](http://www.basf-coatings.com)

Note: BASF RayGloss 402 were tested on LS1 and LS2 clear only

(Coating information continued the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on PHOLUCID 130C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
 Tokyo Club Building,  
 2-6, Kasumigaseki 3-Chome  
 Chiyoda-Ku, Tokyo, 100-0013  
 Japan  
 Telephone: 81-3-3506-3971  
 Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: PHOLUCID 130C was tested on Sabc LS1 clear only.



Information on KUV-5000, KUV-6000 and KUV-9100 coatings may be obtained by writing:

KCC Corporation  
 83 Mabook-Dong, Giheung-Gu, Yongin-Si  
 Gyunggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

Note: KUV-5000 and KUV-9100 was tested on SABIC LS1-111 and SABIC LS2-111 clear only.



**FUJIKURA KASEI**

Information on FUJIHARD HH2540U, FUJIHARD HH3372U and FUJIHARD HH3401U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
 6-15 Shibakeon 2-Chome  
 Minato-Ku, Tokyo, 105-0011  
 Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH2540U was tested on LS2 111S Clear Only.

Note: FUJIHARD HH3372U and FUJIHARD HH3401U were tested on LS1-111 and LS2-111 Clear Only.



Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings may be obtained by writing to the following address:

Mitsubishi Chemical Corporation  
 1-1 Marunouchi, 1-Chome  
 Chiyoda-Ku, Tokyo 100-8251  
 Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Note: Acryking PH-710, Acryking PH-720 and Acryking PH-800 was tested on SABIC LS1-111 only.

Acryking PH-720 and PH-800 was tested on SABIC LS2-111 only.

Acryking PH-930 was tested on SABIC LS1 and LS2 clear only

(Coating information continued the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on UVHC5000, UVHC5000K, and UVHC5000K1 hard coat may be obtained by writing to the following address:

Momentive Performance Materials GmbH  
 Building V7  
 51368 Lverkusen  
 Germany

Momentive Performance Materials Inc.  
 260 Hudson River Road  
 Waterford, NY 12118  
[www.momentive.com](http://www.momentive.com)

Note: UVHC5000 was tested on SABIC LS1 and LS2 clear only.



PAINT & VARNISH COMPANY, INC.

Information on UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 coatings may be obtained by writing to the following address:

Red Spot Paint & Varnish Co., Inc.  
 P.O. Box 418  
 Evansville, IN 47703-0418  
[www.redspot.com](http://www.redspot.com)

Note: UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 was tested on LS1-111/LS2-111 Clear only



Information of X-48-5500-A18 hard coat may be obtained by writing to the following address:

Shin-Etsu Chemical Co., Ltd.  
 4-1, Marunouchi 1-Chome  
 Chiyoda-ku, Tokyo 100-0005,  
 Japan  
[www.shinetsu.co.jp](http://www.shinetsu.co.jp)

Note: X-48-5500-A18 was tested on SABIC LS1-111, 111J and 111H clear only.

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
	SABIC LEXAN® LS1	POLYCARBONATE	111	White &
	Nansha LEXAN® LS2		111S	White &
	China (Coated Only)		111HX	White &
			111X	White &
	<a href="http://www.sabic.com">www.sabic.com</a>			

Coated SABIC Nansha, China plastics may only be treated with the following acceptable coatings applied to the molded lens:

#### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings: See Mitsubishi Chemical Corporation

FUJIHARD HH2540U, FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

KUV-5000, KUV-6000, and KUV-9100: See KCC Corporation

RayGloss 402: See BASF Coatings GmbH

UVHC5000, UVHC5000K, and UVHC5000K1: See Momentive Performance Materials.

UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8: See Red Spot

PHOLUCID 130C: See Chugoku Marine Paints

X-48-5500-A18: See Shin-Etsu Chemical Co., Ltd

#### Coating Manufacturer in Alphabetical Order

Information on RayGloss 402 coatings may be obtained by writing:



BASF Coatings GmbH  
 ECO/DT - C422  
 D-48165 Muenster  
 Germany  
[www.basf-coatings.com](http://www.basf-coatings.com)

Note: BASF RayGloss 402 were tested on LS1 and LS2 clear only

(Coating information continued the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on PHOLUCID 130C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
 Tokyo Club Building,  
 2-6, Kasumigaseki 3-Chome  
 Chiyoda-Ku, Tokyo, 100-0013  
 Japan  
 Telephone: 81-3-3506-3971  
 Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: PHOLUCID 130C was tested on Sabic LS1 clear only.



**FUJIKURA KASEI**

Information on FUJIHARD HH2540U, FUJIHARD HH3372U and FUJIHARD HH3401U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
 6-15 Shibakeon 2-Chome  
 Minato-Ku, Tokyo, 105-0011  
 Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH2540U was tested on LS2 111S Clear Only.

Note: FUJIHARD HH3372U and FUJIHARD HH3401U were tested on LS1-111 and LS2-111 Clear Only.



Information on KUV-5000, KUV-6000 and KUV-9100 coatings may be obtained by writing:

KCC Corporation  
 83 Mabook-Dong, Giheung-Gu, Yongin-Si  
 Gyunggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

Note: KUV-5000, and KUV-9100 was tested on SABIC LS1-111 and SABIC LS2-111 clear only.



**MITSUBISHI  
 CHEMICAL  
 GROUP**

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings may be obtained by writing to the following address:

Mitsubishi Chemical Corporation  
 1-1 Marunouchi, 1-Chome  
 Chiyoda-Ku, Tokyo 100-8251  
 Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Note: Acryking PH-710, Acryking PH-720 and Acryking PH-800 was tested on SABIC LS1-111 only.

Acryking PH-720 and PH-800 was tested on SABIC LS2-111 only.

Acryking PH-930 was tested on SABIC LS1 and LS2 clear only

(Coating information continued the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on UVHC5000, UVHC5000K, and UVHC5000K1 hard coat may be obtained by writing to the following address:

Momentive Performance Materials GmbH  
 Building V7  
 51368 Lverkusen  
 Germany

Momentive Performance Materials Inc.  
 260 Hudson River Road  
 Waterford, NY 12118  
[www.momentive.com](http://www.momentive.com)

Note: UVHC5000 was tested on SABIC LS1 and LS2 clear only.



PAINT & VARNISH COMPANY, INC.

Information on UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 coatings may be obtained by writing to the following address:

Red Spot Paint & Varnish Co., Inc.  
 P.O. Box 418  
 Evansville, IN 47703-0418  
[www.redspot.com](http://www.redspot.com)

Note: UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 was tested on LS1-111/LS2-111 Clear only



Information of X-48-5500-A18 hard coat may be obtained by writing to the following address:

Shin-Etsu Chemical Co., Ltd.  
 4-1, Marunouchi 1-Chome  
 Chiyoda-ku, Tokyo 100-0005,  
 Japan  
[www.shinetsu.co.jp](http://www.shinetsu.co.jp)

Note: X-48-5500-A18 was tested on SABIC LS1-111, 111J and 111H clear only.

---

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------

Sam Yang Corporation	TRIREX 3022L1 (Coated Only)	POLYCARBONATE	100	Clear &
----------------------	--------------------------------	---------------	-----	---------

[www.samyang.com](http://www.samyang.com)

Coated Sam Yang Corporation plastics are only acceptable with the coatings listed below when properly applied to the molded lens.

**Coating in Alphabetical Order and Corresponding Manufacturer**

KUV-4000, KUV-5000 and KUV-9100: See KCC Corporation

**Coating Manufacturer in Alphabetical Order**



Information on KUV-4000, KUV-5000 and KUV-9100 coating may be obtained by writing:

KCC Corporation  
 83 Mabook-Dong, Giheung-Gu, Yongin-Si  
 Gyunggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
Teijin Limited	Panlite L-1225Z Panlite L-1225ZA (Coated Only)	POLYCARBONATE	100 100M	Clear & Clear &

[www.teijin.co.jp](http://www.teijin.co.jp)

#### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-511, Acryking PH-710, Acryking PH-720, Acryking PH-750 Acryking PH-800, Acryking PH-800N5A and Acryking PH-930: See Mitsubishi Chemical Corporation

FUJIHARD HH2540U, FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

KUV-5000: See KCC Corporation

PHOLUCID 180C: See Chugoku Marine Paints, Ltd.

SH-61: See Stanley Electric Co., Ltd.

UVHC5000, UVHC5000K, and UVHC5000K1: See Momentive Performance Materials.

#### Coating Manufacturer in Alphabetical Order



Information on PHOLUCID 180C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
Tokyo Club Building,  
2-6, Kasumigaseki 3-Chome  
Chiyoda-Ku, Tokyo, 100-0013  
Japan  
Telephone: 81-3-3506-3971  
Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: PHOLUCID 180C was tested on Clear Panlite L1225ZA only.



**FUJIKURA KASEI**

Information on FUJIHARD HH2540U, FUJIHARD HH3372U and FUJIHARD HH3401U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
6-15 Shibakeon 2-Chome  
Minato-Ku, Tokyo, 105-0011  
Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH2540U was tested on PANLITE L1225Z 100M Clear Only.

Note: FUJIHARD HH3372U and FUJIHARD HH3401U were tested on PANLITE L1225Z 100 Clear Only.

(Coating information continued the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on KUV-5000 coatings may be obtained by writing:

KCC Corporation  
 83 Mabook-Dong, Giheung-Gu, Yongin-Si  
 Gyunggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

Note: KUV-5000 was tested on Panlite L-1225Z clear only.



MITSUBISHI  
 CHEMICAL  
 GROUP

Acryking PH-511, Acryking PH-710, Acryking PH-720, Acryking PH-750 Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings may be obtained by writing to the following address:

Mitsubishi Chemical Corporation  
 1-1 Marunouchi, 1-Chome  
 Chiyoda-Ku, Tokyo 100-8251  
 Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Note: All Acryking coatings were tested on clear L-1225Z and L-1225ZA



Information on UVHC5000, UVHC5000K, and UVHC5000K1 hard coat may be obtained by writing to the following address:

Momentive Performance Materials GmbH  
 Building V7  
 51368 Lverkusen  
 Germany

Momentive Performance Materials Inc.  
 260 Hudson River Road  
 Waterford, NY 12118  
[www.momentive.com](http://www.momentive.com)

Note: UVHC5000 series was tested on L-1225Z clear only.

Information on Stanley Electric SH-61 may be obtained by writing to the following company:



Stanley Electric Co., Ltd.  
 2-9-13, Nakameguro,  
 Meguro-Ku, Tokyo 153  
 Japan  
[www.stanley.co.jp](http://www.stanley.co.jp)

Note: SH-61 was tested on Panlite L-1225Z 100-M

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
Teijin Polycarbonate China Ltd.	Panlite L-1225Z Panlite L-1225ZA (Coated Only)	POLYCARBONATE	100 100M	Clear & Clear &

[www.teijin.co.jp](http://www.teijin.co.jp)

#### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-511, Acryking PH-710, Acryking PH-720, Acryking PH-750 Acryking PH-800, Acryking PH-800N5A and Acryking PH-930: See Mitsubishi Chemical Corporation

FUJIHARD HH2540U, FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

KUV-5000: See KCC Corporation

PHOLUCID 180C: See Chugoku Marine Paints, Ltd.

SH-61: See Stanley Electric Co., Ltd.

UVHC5000, UVHC5000K, and UVHC5000K1: See Momentive Performance Materials.

#### Coating Manufacturer in Alphabetical Order



Information on PHOLUCID 180C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
Tokyo Club Building,  
2-6, Kasumigaseki 3-Chome  
Chiyoda-Ku, Tokyo, 100-0013  
Japan  
Telephone: 81-3-3506-3971  
Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: PHOLUCID 180C was tested on Clear Panlite L1225ZA only.



Information on FUJIHARD HH2540U, FUJIHARD HH3372U and FUJIHARD HH3401U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
6-15 Shibakeon 2-Chome  
Minato-Ku, Tokyo, 105-0011  
Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH2540U was tested on PANLITE L1225Z 100M Clear Only.

Note: FUJIHARD HH3372U and FUJIHARD HH3401U were tested on PANLITE L1225Z 100 Clear Only.

(Coating information continued the next page)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



Information on KUV-5000 coatings may be obtained by writing:

KCC Corporation  
 83 Mabook-Dong, Giheung-Gu, Yongin-Si  
 Gyunggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

Note: KUV-5000 was tested on Panlite L-1225Z clear only.



Acryking PH-511, Acryking PH-710, Acryking PH-720, Acryking PH-750 Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings may be obtained by writing to the following address:

Mitsubishi Chemical Corporation  
 1-1 Marunouchi, 1-Chome  
 Chiyoda-Ku, Tokyo 100-8251  
 Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Note: All Acryking coatings were tested on clear L-1225Z and L-1225ZA only.



Information on UVHC5000, UVHC5000K, and UVHC5000K1 hard coat may be obtained by writing to the following address:

Momentive Performance Materials GmbH  
 Building V7  
 51368 Lverkusen  
 Germany

Momentive Performance Materials Inc.  
 260 Hudson River Road  
 Waterford, NY 12118  
[www.momentive.com](http://www.momentive.com)

Note: UVHC5000 was tested on L-1225Z clear only.

Information on Stanley Electric SH-61 may be obtained by writing to the following company:



Stanley Electric Co., Ltd.  
 2-9-13, Nakameguro,  
 Meguro-Ku, Tokyo 153  
 Japan  
[www.stanley.co.jp](http://www.stanley.co.jp)

Note: SH-61 was tested on Panlite L-1225Z 100-M

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
Teijin	Panlite L-1225Z	POLYCARBONATE	100	Clear &
Polycarbonate	Panlite L-1225ZA		100M	Clear &
Singapore PTE Ltd.	(Coated Only)			

[www.teijin.co.jp](http://www.teijin.co.jp)

#### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-511, Acryking PH-710, Acryking PH-720, Acryking PH-750, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930: See Mitsubishi Chemical Corporation

FUJIHARD HH2540U, FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

KUV-5000: See KCC Corporation

PHOLUCID 180C: See Chugoku Marine Paints, Ltd.

SH-61: See Stanley Electric Co., Ltd.

UVHC5000, UVHC5000K, and UVHC5000K1: See Momentive Performance Materials.

#### Coating Manufacturer in Alphabetical Order



Information on PHOLUCID 180C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
Tokyo Club Building,  
2-6, Kasumigaseki 3-Chome  
Chiyoda-Ku, Tokyo, 100-0013  
Japan  
Telephone: 81-3-3506-3971  
Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: PHOLUCID 180C was tested on Clear Panlite L1225ZA only.



**FUJIKURA KASEI**

Information on FUJIHARD HH2540U, FUJIHARD HH3372U and FUJIHARD HH3401U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
6-15 Shibakeon 2-Chome  
Minato-Ku, Tokyo, 105-0011  
Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH2540U was tested on PANLITE L1225Z 100M Clear Only.

Note: FUJIHARD HH3372U and FUJIHARD HH3401U were tested on PANLITE L1225Z 100 Clear Only.

(Coating information continued the next page)

**MFR.**                      **TRADE NAME and**  
**FLOW FORMULATION**                      **TYPE OF RESIN**                      **NUMBER**                      **COLOR**



Information on KUV-5000 coatings may be obtained by writing:

KCC Corporation  
83 Mabook-Dong, Giheung-Gu, Yongin-Si  
Gyunggi-Do, South Korea  
[www.kccworld.co.kr](http://www.kccworld.co.kr)

Note: KUV-5000 was tested on Panlite L-1225Z clear only.



Acryking PH-511, Acryking PH-710, Acryking PH-720, Acryking PH-750, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings may be obtained by writing to the following address:

Mitsubishi Chemical Corporation  
1-1 Marunouchi, 1-Chome  
Chiyoda-Ku, Tokyo 100-8251  
Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Note: All Acryking coatings were tested on clear L-1225Z and L-1225ZA only.



Information on UVHC5000, UVHC5000K, and UVHC5000K1 hard coat may be obtained by writing to the following address:

Momentive Performance Materials GmbH  
Building V7  
51368 Lverkusen  
Germany

Momentive Performance Materials Inc.  
260 Hudson River Road  
Waterford, NY 12118  
[www.momentive.com](http://www.momentive.com)

Note: UVHC5000 was tested on L-1225Z clear only.

Information on Stanley Electric SH-61 may be obtained by writing to the following company:



Stanley Electric Co., Ltd.  
2-9-13, Nakameguro,  
Meguro-Ku, Tokyo 153  
Japan  
[www.stanley.co.jp](http://www.stanley.co.jp)

Note: SH-61 was tested on Panlite L-1225Z 100-M

---

---

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
Thai Polycarbonate Co., Ltd. <a href="http://www.tpcc-tpac.com">www.tpcc-tpac.com</a>	IUPIILON ML-300 IUPIILON ML-300AH (Coated Only)	POLYCARBONATE	001	Clear &

Coated Thai Polycarbonate Co., Ltd. Iupilon plastics may only be treated with the following coatings listed below.

#### Coating in Alphabetical Order and Corresponding Manufacturer

Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930: See Mitsubishi Chemical Corporation

FUJIHARD HH3372U, FUJIHARD HH3401U: See Fujikura Kasei Co., Ltd.

PHOLUCID 180C and PHOLUCID 185C: See Chugoku Marine Paints, Ltd.

SH-61: See Stanley Electric Co., Ltd.

#### Coating Manufacturer in Alphabetical Order



Information on PHOLUCID 180C and PHOLUCID 185C coatings may be obtained by writing:

Chugoku Marine Paints, Ltd.  
Tokyo Club Building,  
2-6, Kasumigaseki 3-Chome  
Chiyoda-Ku, Tokyo, 100-0013  
Japan  
Telephone: 81-3-3506-3971  
Facsimile: +81-3-5511-8542  
[www.cmp.co.jp](http://www.cmp.co.jp)

Note: PHOLUCID 180C and PHOLUCID 185C was tested on Clear IUPIILON ML-300AH only.



Information on FUJIHARD HH3372U and FUJIHARD HH3401U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
6-15 Shibakeon 2-Chome  
Minato-Ku, Tokyo, 105-0011  
Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH3401U was tested on Clear IUPIILON ML-300 and IUPIILON ML-350 only

(Coating Information Continued on Next Page.)

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
-------------	--	----------------------	---------------	--------------



**MITSUBISHI CHEMICAL GROUP**

Information on Acryking PH-710, Acryking PH-720, Acryking PH-800, Acryking PH-800N5A and Acryking PH-930 coatings may be obtained by writing to the following company:

Mitsubishi Chemical Corporation  
 1-1 Marunouchi, 1-Chome  
 Chiyoda-Ku, Tokyo 100-8251 Japan  
[www.m-chemical.co.jp](http://www.m-chemical.co.jp)

Information on Stanley Electric SH-61 may be obtained by writing to the following company:



Stanley Electric Co., Ltd.  
 2-9-13, Nakameguro,  
 Meguro-Ku, Tokyo 153  
 Japan  
[www.stanley.co.jp](http://www.stanley.co.jp)

Note: SH-61 was tested on ML-300

Thai Polycarbonate Co., Ltd.	IUPILON ML-350 (Coated Only)	POLYCARBONATE	001	Clear &
------------------------------	------------------------------	---------------	-----	---------

[www.tpcc-tpac.com](http://www.tpcc-tpac.com)

Coated Thai Polycarbonate Co., Ltd. Iupilon ML-350 plastics may only be treated with the following coatings listed below.

### Coating in Alphabetical Order and Corresponding Manufacturer

FUJIHARD HH3372U, FUJIHARD HH3401U : See Fujikura Kasei Co., Ltd.

### Coating Manufacturer in Alphabetical Order



Information on FUJIHARD HH3372U and FUJIHARD HH3401U coatings may be obtained by writing:

Fujikura Kasei Co., Ltd.  
 6-15 Shibakeon 2-Chome  
 Minato-Ku, Tokyo, 105-0011  
 Japan  
[www.fkkasei.co.jp](http://www.fkkasei.co.jp)

Note: FUJIHARD HH3401U was tested on Clear IUPILON ML-300 and IUPILON ML-350 only

<u>MFR.</u>	<u>TRADE NAME and FLOW FORMULATION</u>	<u>TYPE OF RESIN</u>	<u>NUMBER</u>	<u>COLOR</u>
Wanhua Chemical Group Co., Ltd. No. 59 Chongqing Street YEDA, Yantai, Shandong P. R. China <a href="http://www.whchem.com">www.whchem.com</a>	ACRYPLAS® HD01	Polymethyl Methacrylate		Clear

---

Wanhua Chemical Group Co., Ltd. No. 59 Chongqing Street YEDA, Yantai, Shandong P. R. China <a href="http://www.whchem.com">www.whchem.com</a>	HL6157	Polycarbonate	9103	Clear Q
---	--------	---------------	------	---------

Wanhua Chemical Group Co., Ltd. polycarbonate plastics are only acceptable with the coatings listed below when properly applied to the molded lens.

#### Coating in Alphabetical Order and Corresponding Manufacturer

UVT820V Series: See Red Spot.

#### Coating Manufacturer in Alphabetical Order



**PAINT & VARNISH COMPANY, INC.**

Red Spot Paint & Varnish Co., Inc.  
P.O. Box 418  
Evansville, IN 47703-0418  
[www.redspot.com](http://www.redspot.com)

Information on UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 coatings may be obtained by writing to the following address:

Note: Red Spot UVT820V1, UVT820V2, UVT820V3, UVT820V4, UVT820V5, UVT820V6, UVT820V7 and UVT820V8 was tested on clear HL6157.

---

## INDEX OF COMPANIES and MATERIALS

### A

Acryking PH-511, 50, 51, 52, 53, 54, 55  
Acryking PH-710, 9, 10, 13, 18, 21, 22,  
25, 26, 28, 29, 31, 32, 34, 35, 37, 38,  
40, 41, 43, 44, 46, 47, 50, 51, 52, 53,  
54, 55, 56, 57  
Acryking PH-720, 9, 10, 13, 18, 19, 21,  
22, 25, 26, 28, 29, 31, 32, 34, 35, 37,  
38, 40, 41, 43, 44, 46, 47, 50, 51, 52,  
53, 54, 55, 56, 57  
Acryking PH-750, 50, 51, 52, 53, 54, 55  
Acryking PH-800, 9, 10, 13, 15, 17, 18,  
19, 21, 22, 25, 26, 28, 29, 31, 32, 34,  
35, 37, 38, 40, 41, 43, 44, 46, 47, 50,  
51, 52, 53, 54, 55, 56, 57  
Acryking PH-800N5A, 9, 10, 13, 15,  
17, 18, 19, 21, 22, 25, 26, 28, 29, 31,  
32, 34, 35, 37, 38, 40, 41, 43, 44, 46,  
47, 50, 51, 52, 53, 54, 55, 56, 57  
Acryking PH-930, 9, 10, 18, 19, 21, 22,  
25, 26, 28, 29, 31, 32, 34, 35, 37, 38,  
40, 41, 43, 44, 46, 47, 51, 53, 55, 57  
ACRYLITE® Resist AG100, 24  
ACRYPLAS® HD01, 58  
Appendix A  
AMECA Accredited Laboratory Information, 62

### B

BASF Coatings GmbH, 9, 10, 25, 28,  
31, 34, 37, 40, 43, 46

### C

Chugoku Marine Paints, 9, 10, 18, 21,  
25, 26, 28, 29, 31, 32, 34, 35, 37, 38,  
40, 41, 43, 44, 46, 47, 50, 52, 54, 56  
Covestro (Hong Kong) Limited (Asia  
Pacific), 9  
Covestro (Hong Kong) Limited., 9  
Covestro Deutschland AG, 9  
Covestro Deutschland AG (Europe), 9  
Covestro LLC (America), 9

### F

Formosa Idemitsu Petrochemical  
Corp., 13  
FUJIHARD HH2540U, 9, 11, 18, 21, 25,  
26, 28, 29, 31, 32, 34, 35, 37, 38, 40,  
41, 43, 44, 46, 47, 50, 52, 54, 56  
FUJIHARD HH3372U, 18, 20, 21, 23,  
25, 26, 28, 29, 31, 32, 34, 35, 37, 38,  
40, 41, 43, 44, 46, 47, 50, 52, 54, 56, 57  
FUJIHARD HH3401U, 9, 11, 18, 20, 21,  
23, 25, 26, 28, 29, 31, 32, 34, 35, 37,  
38, 40, 41, 43, 44, 46, 47, 50, 52, 54,  
56, 57  
Fujikura Kasei Co., Ltd., 9, 18, 20, 21,  
23, 25, 28, 31, 34, 37, 40, 43, 46, 50,  
52, 54, 56, 57

### I

IUPILON ML-300, 18, 20, 21, 23, 56, 57  
IUPILON ML-350, 18, 20, 23, 56, 57

### K

KCC Corporation, 9, 25, 28, 31, 37, 43,  
46, 49  
KUV-4000, 9  
KUV-5000, 9, 11, 15, 17, 25, 26, 28, 29,  
31, 32, 34, 35, 37, 38, 40, 41, 43, 44,  
46, 47, 49, 50, 51, 52, 53, 54, 55  
KUV-6000, 9, 11, 25, 26, 28, 29, 31, 32,  
34, 35, 37, 38, 40, 41, 43, 44, 46, 47, 49  
KUV-9100, 25, 26, 28, 29, 31, 32, 34,  
35, 37, 38, 40, 41, 43, 44, 46, 47, 49

### L

LG Chem, Ltd, 14  
Lotte Chemical Corp., 15, 17  
LT-1100, 15  
LT-1220, 15, 17

### M

MAKROLON, 9  
Mitsubishi Chemical Corporation, 9,  
13, 15, 17, 18, 21, 24, 25, 34, 37, 40,  
43, 46, 50, 52, 54, 56

Mitsubishi Engineering Plastics, 18, 20  
Mitsubishi Gas Chemical (Shanghai) Plastics Corp., Ltd., 21, 23  
Momentive Performance Materials, 9, 11, 24, 25, 27, 28, 30, 31, 33, 34, 36, 37, 39, 40, 42, 43, 45, 46, 48, 50, 51, 52, 53, 54, 55

## P

Panlite, 50, 51, 52, 54  
PHC XH100P, 24  
PHOLUCID, 9, 10, 18, 21, 26, 29, 32, 35, 38, 41, 50, 52, 54, 56  
PHOLUCID 130C, 9, 10, 25, 26, 28, 29, 31, 32, 34, 35, 37, 38, 40, 41, 43, 44, 46, 47  
PHOLUCID 180C, 10, 18, 21, 50, 52, 54, 56  
PHOLUCID 185C, 21, 56  
PLEXIGLAS® Resist AG1000, 24

## R

RayGloss 400, 9, 25, 28, 31, 34, 37, 40, 43, 46  
RayGloss 401, 9, 25  
RayGloss 402, 9, 10, 25, 28, 31, 34, 37, 40, 43, 46  
Red Spot Paint & Varnish Co., Inc., 9, 28, 31, 34, 37, 40, 43, 46, 58  
Roehm America LLC, 24  
Roehm Chemical (Shanghai) Co., Ltd., 24  
Röhm GmbH, 24

## S

SABIC Brazil, 28  
SABIC Chongqing, China, 31  
SABIC Europe, 34  
SABIC India, 40  
SABIC Japan, 37  
SABIC Korea, 43  
SABIC Nansha, China, 46  
SABIC USA, 25  
Sam Yang Corporation, 49  
SH-61, 9, 12, 18, 19, 20, 22, 50, 51, 52, 53, 54, 55, 56, 57  
Shin-Etsu Chemical Co., Ltd, 28, 31, 34, 37, 40, 43, 46

Shin-Etsu Chemical Co., Ltd., 25, 27, 28, 30, 31, 33, 34, 36, 39, 40, 42, 43, 45, 48  
SH-K142, 14  
SH-K151, 14  
SHP470FT/AS4700, 9, 11  
Stanley Electric Co., Ltd., 12, 14, 19, 20, 22, 51, 53, 55, 57

## T

TARFLON, 13  
Teijin Limited, 50  
Teijin Polycarbonate China Ltd., 52  
Teijin Polycarbonate Singapore PTE Ltd., 54  
Thai Polycarbonate Co., Ltd., 56, 57

## U

UVHC5000, 9, 11, 25, 27, 28, 30, 31, 33, 34, 36, 37, 39, 40, 42, 43, 45, 46, 48, 50, 51, 52, 53, 54, 55  
UVHC5000K, 9, 11, 25, 27, 28, 30, 31, 33, 34, 36, 37, 39, 40, 42, 43, 45, 46, 48, 50, 51, 52, 53, 54, 55  
UVHC5000K1, 9, 11, 25, 27, 28, 30, 31, 33, 34, 36, 37, 39, 40, 42, 43, 45, 46, 48, 50, 51, 52, 53, 54, 55  
UVT820V, 58  
UVT820V1, 11, 15, 16, 25, 27, 28, 30, 31, 33, 34, 36, 37, 39, 40, 42, 43, 45, 46, 48, 58  
UVT820V2, 9, 11, 15, 16, 25, 27, 28, 30, 31, 33, 34, 36, 37, 39, 40, 42, 43, 45, 46, 48, 58  
UVT820V3, 9, 11, 15, 16, 25, 27, 28, 30, 31, 33, 34, 36, 37, 39, 40, 42, 43, 45, 46, 48, 58  
UVT820V4, 9, 11, 15, 16, 25, 27, 28, 30, 31, 33, 34, 36, 37, 39, 40, 42, 43, 45, 46, 48, 58  
UVT820V5, 9, 11, 15, 16, 25, 27, 28, 30, 31, 33, 34, 36, 37, 39, 40, 42, 43, 45, 46, 48, 58  
UVT820V6, 9, 11, 15, 16, 25, 27, 28, 30, 31, 33, 34, 36, 37, 39, 40, 42, 43, 45, 46, 48, 58  
UVT820V7, 9, 11, 15, 16, 25, 27, 28, 30, 31, 33, 34, 36, 37, 39, 40, 42, 43, 45, 46, 48, 58

**UVT820V8, 9, 11, 15, 16, 25, 27, 28, 30,  
31, 33, 34, 36, 37, 39, 40, 42, 43, 45,  
46, 48, 58**

**X**

**X-48-5500-A18, 25, 27, 28, 30, 31, 33,  
34, 36, 37, 39, 40, 42, 43, 45, 46, 48**

**W**

**Wanhua Chemical Group Co., Ltd., 58**

## Appendix A: AMECA Accredited Laboratory Information

Atlas Weathering Services Group  
DSET Laboratories  
45601 N. 47th Avenue  
Phoenix, Arizona 85027-7042  
**Tel:** (623) 465-7356; (800) 255-DSET  
**FAX:** (623) 465-9409  
**Website:** [www.atlaswsg.com](http://www.atlaswsg.com)

Atlas Weathering Services Group  
South Florida Test Services  
Everglades Division  
16100 S.W. 216th Street  
Miami, Florida 33170  
**Tel:** (305) 245-3659  
**FAX:** (305) 245-9122  
**Website:** [www.atlaswsg.com](http://www.atlaswsg.com)

Q-Lab Arizona Test Services  
21212 W Patton Rd,  
Wittmann, AZ 85361  
**Tel:** (623) 386-5140  
**FAX:** (623) 386-5143  
**Website:** [www.q-lab.com](http://www.q-lab.com)

Q-Lab Florida Test Services and  
1005 S.W. 18th Avenue,  
P.O. Box 349490  
Homestead, Florida 33034  
**Tel:** (305) 245-5600  
**FAX:** (305) 245-5656  
**Website:** [www.q-lab.com](http://www.q-lab.com)

## Appendix B: Federal Standard for Plastics

### Definitions in FMVSS 108

**Coated materials** means a material which has a coating applied to the surface of the finished sample to impart some protective properties. Coating identification means a mark of the manufacturer's name, formulation designation number, and recommendations for application.

**Color** Fundamental definitions of color are expressed by Chromaticity Coordinates according to the CIE 1931 Standard Colorimetric System, as described in the CIE 1931 Chromaticity Diagram (incorporated by reference, see § 571.5).

**Color bleeding** means the migration of color out of a plastic part onto the surrounding surface.

**Cracking** means a separation of adjacent sections of a plastic material with penetration into the specimen.

**Crazing** means a network of apparent fine cracks on or beneath the surface of materials.

**Exposed** means material used in lenses or optical devices exposed to direct sunlight as installed on the vehicle.

### Excerpts from Section 14 from FMVSS 108

#### Plastic and Coating Requirements

S14.1.2 Plastic optical materials. All plastic materials used for optical parts such as lenses and reflectors on lamps or reflective devices required or allowed by this standard must conform to the material test requirements of S14.4.2.

S14.1.3 All coatings used on optical materials must have added to their formulations an optical brightener, whose presence is detectable by ultraviolet light, to aid in testing for their presence. Other equivalent industry accepted methods may be used as an alternative.

#### Color Specifications

S14.4.1 *Color test.* The requirement applies to the overall effective color of light emitted by the device and not to the color of the light from a small area of the lens. It does not apply to any pilot, indicator, or tell-tale lights. The color of the sample device must comply when tested by either the Visual Method or the Tristimulus Method.

S14.4.1.3 *Visual method.*

S14.4.1.3.1 *Visual method procedure.* The color of light from the sample device must be compared visually with the color of the light from a standard. The standard may consist of a filter or limit glass. In the case of white, CIE Source A is used only as a color reference. The chromaticity coordinates of the color standards must be as close as possible to the limits listed. The color of the standard filters is determined spectro-photometrically.

S14.4.1.3.2 *Visual method performance requirements.* The color must comply with the applicable requirement.

S14.4.1.3.2.1 *Red.* Red is not acceptable if it is less saturated (paler), yellower, or bluer than the limit standards.

S14.4.1.3.2.2 *Yellow (Amber)*. Yellow is not acceptable if it is less saturated (paler), greener, or redder than the limit standards.

S14.4.1.3.2.3 *White*. White is not acceptable if its color differs materially from that of CIE Source A.

S14.4.1.3.2.4 *Green*. Green is not acceptable if it is less saturated (paler), yellower, or bluer than the limit standards.

S14.4.1.3.2.5 *Blue*. Blue is not acceptable if it is less saturated (paler), greener, or redder than the limit standards.

#### S14.4.1.4 *Tristimulus method*.

##### S14.4.1.4.1 *Tristimulus method procedure*.

S14.4.1.4.1.1 The color of light from the H–V point of a sample device must be measured by photoelectric receivers with spectral responses that approximate CIE standard spectral tristimulus values.

S14.4.1.4.1.2 A sphere may be used to integrate light from a colored source provided that the color shift that results from the spectral selectivity of the sphere paint be corrected by the use of a filter, correction factor, or an appropriate calibration.

S14.4.1.4.1.3 Where the sample device does not have uniform spectral characteristics in all useful directions, color measurements must be made at as many directions of view as are required to evaluate the color for those directions that apply to the end use of the device.

S14.4.1.4.2 *Tristimulus method performance requirements*. The color must comply with the applicable requirement.

S14.4.1.4.2.1 *Red*. The color of light emitted must fall within the following boundaries:

$$y = 0.33 \text{ (yellow boundary)}$$

$$y = 0.98 - x \text{ (purple boundary)}$$

S14.4.1.4.2.2 *Yellow (Amber)*. The color of light emitted must fall within the following boundaries:

$$y = 0.39 \text{ (red boundary)}$$

$$y = 0.79 - 0.67x \text{ (white boundary)}$$

$$y = x - 0.12 \text{ (green boundary)}$$

S14.4.1.4.2.3 *White (achromatic)*. The color of light emitted must fall within the following boundaries:

$$x = 0.31 \text{ (blue boundary)}$$

$$y = 0.44 \text{ (green boundary)}$$

$$x = 0.50 \text{ (yellow boundary)}$$

$$y = 0.15 + 0.64x \text{ (green boundary)}$$

$y = 0.38$  (red boundary)  
 $y = 0.05 + 0.75x$  (purple boundary)

*S14.4.1.4.2.4 Green.* The color of light emitted must fall within the following boundaries:

$y = 0.73 - 0.73x$  (yellow boundary)  
 $x = 0.63y - 0.04$  (white boundary)  
 $y = 0.50 - 0.50x$  (blue boundary)

*S14.4.1.4.2.5 Restricted Blue.* The color of light emitted must fall within the following boundaries:

$y = 0.07 + 0.81x$  (green boundary)  
 $x = 0.40 - y$  (white boundary)  
 $x = 0.13 + 0.60y$  (violet boundary)

*S14.4.1.4.2.6 Signal Blue.* The color of light emitted must fall within the following boundaries:

$y = 0.32$  (green boundary)  
 $x = 0.16$  (white boundary)  
 $x = 0.40 - y$  (white boundary)  
 $x = 0.13 + 0.60y$  (violet boundary)

### ***Plastic optical materials tests***

*S14.4.2 Plastic optical materials tests.* Accelerated weathering procedures are not permitted.

*S14.4.2.1 Samples.*

*S14.4.2.1.1* Samples of materials shall be injection molded into polished metal molds to produce test specimens with two flat and parallel faces. Alternative techniques may be used to produce equivalent specimens.

*S14.4.2.1.2* Test specimens shape may vary, but each exposed surface must contain a minimum uninterrupted area of 32 sq cm.

*S14.4.2.1.3* Samples must be furnished in thicknesses of 1.6 +/- 0.25 mm, 2.3 +/- 0.25 mm, 3.2 +/- 0.25 mm, and 6.4 +/- 0.25 mm. *S14.4.2.1.4* All samples must conform to the applicable color test requirement of this standard prior to testing.

*S14.4.2.1.5* A control sample, kept properly protected from influences which may change its appearance and properties of each thickness, must be retained.

*S14.4.2.2 Outdoor exposure test.*

*S14.4.2.2.1* Outdoor exposure tests of 3 years in duration must be made on samples of all materials, including coated and uncoated versions, used for optical parts of devices covered by this standard. Tests are to be conducted in Florida and Arizona.

S14.4.2.2.2 Concentrations of polymer components and additives used in plastic materials may be changed without outdoor exposure testing provided the changes are within the limits of composition represented by higher and lower concentrations of these polymer components and additives previously tested to this section and found to meet its requirements.

S14.4.2.2.3 Procedure. S14.4.2.2.3.1 One sample of each thickness of each material must be mounted at each exposure site so that at least a minimum uninterrupted area of 32 sq cm of the exposed upper surface of the sample is at an angle of 45 degrees to the horizontal facing south. The sample must be mounted in the open no closer than 30 cm (11.8 in) to its background.

S14.4.2.2.3.2 During the exposure time the samples must be cleaned once every three months by washing with mild soap or detergent and water, and then rinsing with distilled water. Rubbing must be avoided.

S14.4.2.2.4 *Performance requirements.* Plastic lenses, other than those incorporating reflex reflectors, used for inner lenses or those covered by another material and not exposed directly to sunlight must meet the optical material test requirements when covered by the outer lens or other material.

S14.4.2.2.4.1 After completion of the outdoor exposure test the haze and loss of surface luster as measured by ASTM D1003–92 (incorporated by reference, see § 571.5) must not be greater than:

- (a) 30% for materials used for outer lenses, other than those incorporating reflex reflectors;
- (b) 7% for materials used for reflex reflectors and lenses used in front of reflex reflectors.

S14.4.2.2.4.2 After completion of the outdoor exposure test materials used for headlamp lenses must show no deterioration.

S14.4.2.2.4.3 After completion of the outdoor exposure test all materials, when compared with the unexposed control samples, must not show physical changes affecting performance such as color bleeding, delamination, crazing, or cracking. Additionally materials used for reflex reflectors and lenses used in front of reflex reflectors must not show surface deterioration or dimensional changes.

S14.4.2.2.4.4 After completion of the outdoor exposure test all materials, when compared with the unexposed control samples, must not have their luminous transmittance changed by more than 25% when tested in accordance with ASTM E308–66 (incorporated by reference, see § 571.5) using CIE Illuminant A (2856K). S14.4.2.2.4.5 After completion of the outdoor exposure test all materials must conform to the color test of this standard in the range of thickness stated by the material manufacturer.

S14.4.2.3 *Heat test.*

S14.4.2.3.1 *Procedure.* Two samples of each thickness of each material must be supported at the bottom, with at least 51 mm of the sample above the support, in the vertical position in such a manner that, on each side, the minimum uninterrupted area of exposed surface is not less than 3225 sq mm. The samples are placed in a circulating air oven at 79 Degrees +/- 3 Degrees for Two hours.

S14.4.2.3.2 *Performance requirements.*

After completion of the heat exposure and cooling to room ambient temperature, a test specimen must show no change in shape and general appearance discernable to the naked eye when compared with an unexposed specimen and continue to conform to the applicable color test requirement of this standard.

*Appendix C: DOT Interpretation Files and Supplemental Lab Information*